



Leon County

Board of County Commissioners

301 South Monroe Street, Tallahassee, Florida 32301
(850) 606-5302 www.leoncountyfl.gov

Purchasing Division
2284 Miccosukee Road
Tallahassee, Florida 32308
(850) 606-1600

Commissioners

BILL PROCTOR
District 1

JANE G. SAULS
District 2

JOHN DAILEY
District 3

BRYAN DESLOGE
District 4

BOB RACKLEFF
District 5

CLIFF THAELL
At-Large

AKIN AKINYEMI
At-Large

PARWEZ ALAM
County Administrator

HERBERT W.A. THIELE
County Attorney

March 10, 2010

RE: Northeast Branch Library Addition, Bid No: BC-03-11-10-19
Opening Date: ~~Thursday, March 11, 2010 at 2:00 PM~~
Revised to Wednesday, March 17, 2010 at 2:00 PM

ADDENDUM #5

Dear Contractor:

This letter serves as Addendum #5 for the above referenced project.

1. The bid due date is being revised to Wednesday, March 17, 2010 at 2:00 PM.
2. Attached is the missing appendix to specification section 15900, Building Automation System.

Acknowledgment of this addendum is required as part of your bid submittal. Failure to acknowledge this addendum may result in rejection of your bid.

Should you have any questions, feel free to call me at (850) 606-1600.

Sincerely,

Keith M. Roberts
Purchasing Director

ABBREVIATIONS

AFD	ADJUSTABLE FREQUENCY DRIVE
AHU	AIR HANDLING UNIT
AI	ANALOG INPUT
AO	ANALOG OUTPUT
AVG	AVERAGING SENSOR
BI	BINARY INPUT
BO	BINARY OUTPUT
C	RELAY COIL
C/C	COOLING COIL
CE	CARBON DIOXIDE SENSOR / TRANSMITTER
CNT	CONTACTOR
CS	CURRENT SWITCH
CV	COOLING VALVE
D	DAMPER
DP	DIFFERENTIAL PRESSURE SENSOR / TRANSMITTER
DPS	DIFFERENTIAL PRESSURE SWITCH
FE	FLOW SENSOR / TRANSMITTER
H/C	HEATING COIL
HE	HUMIDITY SENSOR
LAN	LOCAL AREA NETWORK
LTF	LOW TEMPERATURE FREEZESTAT
N.C.	NORMALLY CLOSED
N.O.	NORMALLY OPEN
OA	OUTSIDE AIR
OAD	OUTSIDE AIR DAMPER
R	RELAY
RA	RETURN AIR
SA	SUPPLY AIR
SD	SMOKE DETECTOR
SF	SUPPLY FAN
SP	STATIC PRESSURE SENSOR / TRANSMITTER
TE	TEMPERATURE SENSOR / TRANSMITTER
V	VALVE
----	24V CONTROL WIRING
———	120V CONTROL WIRING



NE BRANCH LIBRARY

**ABBREVIATIONS -
CONTROLS**

114 EAST 20 AVENUE, SUITE 200, FT. LAUDERDALE, FL 33301
 TEL: 954.343.1111
 WWW.A2EENGINEERING.COM
 THE PROJECT NO. 0907
 THIS DOCUMENT IS THE PROPERTY OF A2E ENGINEERING, INC.
 IT IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY
 IDENTIFIED WITH THIS DRAWING. IT IS NOT TO BE REPRODUCED,
 COPIED, OR TRANSMITTED IN ANY MANNER WITHOUT THE WRITTEN
 PERMISSION OF A2E ENGINEERING, INC.
 Florida Certificate of Authorization #2485



PROJECT	09-27
DATE	12/15/09
DRAWN	REM
CHECKED	DMH/RLC
FILE NO.	.

REV	DATE
△	/ /

DRAWING NO.
C-1
 SHEET
 OF

A-1 AIR HANDLING UNIT CONTROL (AHU-3):

1. General

- a. The air handling unit shall be controlled by a stand-alone building or advanced application controller. Sequence of operation shall not rely on a communication interface with a remote panel; all control logic shall reside in control panel serving equipment.
- b. The unit controller shall reside on a Peer-to-Peer Building Level Network as defined in Article 2.2 "Communications" of Specification 15900.

2. Run Conditions

- a. Occupied Mode: Enable the air handling unit based on a user definable occupied time schedule.
- b. Unoccupied Mode
 - 1) Humidity Control: If space humidity rises above setpoint during unoccupied hours; then initiate an unoccupied dehumidification mode of operation until space humidity is below setpoint minus a deadband.
 - 2) Tenant Override: If the override button is activated from any terminal unit ASC; then initiate an occupied mode of operation for a minimum time delay.
 - 3) Associated Equipment: If the system is initiated during unoccupied hours; then all other equipment (pumps, chiller, etc.) that is required for occupied operation shall be placed into a mode of occupied operation as defined in their respective sequences of operation.
- c. Dehumidification Mode: If the space humidity is above setpoint plus a deadband; then enter unoccupied dehumidification mode until the space humidity is below setpoint minus a deadband.

3. Supply Fan

- a. Start/Stop: Start/stop of the supply fan shall be controlled through the H-O-A switch on the adjustable frequency drive (AFD). Enable the supply fan based on an occupied time schedule or unoccupied overrides.
- b. Status: Supply fan operation shall be proved through a current switch. Upon failure, the BAS shall annunciate one of the following alarms (manual reset):
 - 1) Supply Fan Failure: If the fan is commanded on, but the status is off.
 - 2) Supply Fan in Hand Mode: If the fan is commanded off, but the status is on.
- c. Speed: Once enabled; the AFD shall ramp the supply fan speed to operating setpoint over a 60 second time delay (Program ramp time in AFD).

- 1) Supply Air Static Pressure Control: Modulate supply fan speed to maintain a duct static pressure setpoint. Static pressure shall be measured by a sensor located approximately 2/3 down the longest duct run or as indicated on the drawings.
 - a) Static Pressure Reset: Continuously poll all of the variable volume terminals served by the air handling unit and calculate a sliding window average of the maximum damper position. Reset the static pressure setpoint based on maximum damper position. If communication between the terminal unit ASCs and the air handling unit CAC is failed; then revert to a default value.
 - 2) Maximum Fan Speed Reset: If the outside air damper is open greater than 95% and the return air damper is at minimum position and outside airflow rate is below setpoint for a minimum time delay, then reset minimum fan speed setpoint to maintain outside airflow setpoint.
4. Outside Air Damper
- a. Enable/Disable: If the supply fan is enabled during occupied hours; then modulate the outside air damper to maintain an outside air flow setpoint. If the supply fan is enabled during unoccupied hours or is shut down; then close the outside air damper.
 - 1) Alarms: The BAS shall annunciate the following alarms (auto reset):
 - a) High Outside Air Flow: If the outside air flow is 20% (adj.) greater than setpoint for a minimum time delay.
 - b) Low Outside Air Flow: If the outside air flow is 20% (adj.) less than setpoint for a minimum time delay.
 - c) High CO2 Concentration: If the CO2 level is greater than setpoint for a minimum time delay.
 - 2) Outside Airflow Target Reset:
 - a) Provide a minimum and maximum outside airflow setpoint. Reset the outside airflow setpoint to maintain indoor CO₂ concentration setpoint.
5. Return Air Damper: If the outside air damper position is greater than 95% open for a minimum time delay and if outside air flow is below setpoint; then modulate the return air damper to maintain the outside airflow setpoint. Provide a minimum damper position setpoint.
6. Cooling Valve
- a. Enable/Disable: If the supply fan is on; then enable the cooling valve. If the supply fan is off; then close the cooling valve.
 - b. Supply Temperature Control: Modulate the cooling valve to maintain a supply air temperature target.

- 1) Alarms: The BAS shall annunciate the following alarms (auto reset):
 - a) High Supply Air Temperature: If the supply air temperature is 5 °F (adj.) greater than setpoint for a minimum time delay.
 - b) Low Supply Air Temperature: If the supply air temperature is 5 °F (adj.) less than setpoint for a minimum time delay.

Supply Temperature Target Reset: Continuously poll each of the variable volume terminals and calculate the differential between space temperature and control setpoint. Calculate a sliding window average of the calculated differentials and reset the supply air discharge setpoint to maintain a zero average. Concurrently reset the supply air setpoint to maintain a return air humidity setpoint. Reset the supply air setpoint to the minimum output of the two reset schemes.

- c) Dehumidification Mode: During dehumidification mode, override supply temperature control and modulate cooling valve to full open position.


7. Electric Preheat (EDH-3)

- a) Enable/Disable: If the supply fan is on; then enable the electric preheat. If the supply fan is off; then disable the electric preheat.
- b) Supply Temperature Control: Stage the electric preheat to maintain a mixed air temperature setpoint minus a deadband.

8. Safeties

- a) Smoke Detector(s): Smoke detector is provided by others but shall be wired to an auxiliary contact on the AFD to shut down the air handler fan upon detection of smoke.
- b) High Pressure Limit: Provide a pressure switch at the supply fan discharge, wired to an auxiliary contact on the AFD. If static pressure exceeds 3.0 in. w.g, the switch shall override all controls and shut down the unit.
- c) Low Temperature Limit Thermostat: If the chilled water coil entering air temperature is less than 35°F; then shut down the supply fan. The low limit thermostat shall be hard wired to an auxiliary contact on the AFD to override all controls.
- d) Float Switch: Provide a float switch in the auxiliary drain pan wired to an auxiliary contact on the AFD.


9. Miscellaneous Alarms: The BAS shall announce the following alarms:
- a. Dirty Filter: If the differential pressure across the filter is greater than 1.0" w.g. (adj.) for a minimum time delay.
 - b. Low Mixed Air Temperature: If the mixed air temperature is less than 35 °F (adj.) for a minimum time delay.
10. Required Reports
- a. Title: Air Handling Unit Failure
Frequency: Upon failure of supply fan
Data: Instantaneous value of all points on air handling unit.
 - b. Title: Runtime Report
Frequency: Weekly
Data: The runtime hours per day for the supply fan.
 - c. Title: Return Air Temperature
Frequency: Weekly
Data: Low, high, and average return air temperature per day.



NOTES:

1. FIELD VERIFY ALL WIRING TERMINATIONS.
2. FIELD VERIFY ALL CONNECTIONS.

ADJUSTABLE FREQUENCY DRIVE -- WIRING DETAIL



NE BRANCH LIBRARY

AHU-3 - CONTROLS

114 EAST 5TH AVENUE, TALLAHASSEE, FL
 32304
 TEL: 904.224.1111
 FAX: 904.224.1112
 WWW.BARNETTFRONZAKBARLOWE.COM

THE PROJECT NO. 0927
 IS THE PROPERTY OF AN INSTRUMENT OF SERVICE TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED HEREIN. ANY REUSE OR MODIFICATION WITHOUT WRITTEN PERMISSION IS PROHIBITED.

Florida Certificate of Authorization #2485



PROJECT 09-27
 DATE 12/15/09
 DRAWN REM
 CHECKED DMH/RLC
 FILE NO. .

REV	DATE
Δ / /	/ /

DRAWING NO. **C-2**
 SHEET OF

A-1 FAN POWERED TERMINAL UNIT WITH ELECTRIC HEAT (FTU):

1. General

- a. The terminal unit shall be controlled by a standalone ASC. The ASC shall monitor and control the unit in a stand-alone mode or as directed by the BAS.
- b. The ASC reside on a sub-network as defined in Article 2.2 "Communications" of Specification 15900.

2. Run Conditions

- a. Occupied Mode: Enable the terminal unit based on a user definable occupied time schedule. Enable heating and cooling modes of operation to maintain the occupied setpoints.
- b. Unoccupied Mode:
 - 1) Temperature Control: During unoccupied hours reset the heating and cooling setpoints equal to the respective unoccupied setpoints. Enable heating and cooling modes of operation to maintain the unoccupied setpoints. If unoccupied mode is enabled; then send signal to respective air handler AAC to initiate unoccupied operation.
 - 2) Tenant Override: If the override button is activated at the space sensor; then initiate an occupied mode of operation for a minimum time delay. If tenant override is enabled; then send signal to respective air handler AAC to initiate occupied operation.
- c. Cooling / Heating Changeover
 - 1) Heating Mode: If primary airflow is at the minimum airflow setpoint and space temperature is below heating setpoint; then change to Heating Mode.
 - 2) Cooling Mode: If space temperature is above cooling setpoint; then change to Cooling Mode.

3. Inlet Damper


- a. Enable/Disable: The inlet damper shall be enabled during heating and cooling modes of operation.
- b. Airflow Setpoints: Provide minimum and maximum airflow setpoints. (Initial value: See Terminal Box Schedule).
- c. Space Setpoints: Provide a space temperature cooling setpoint. Heating setpoint shall be equal to the cooling setpoint minus a deadband. Provide unoccupied heating and cooling setpoint.
- d. Cooling Mode: Modulate inlet damper between minimum and maximum airflow setpoints to maintain space setpoint.
- e. Heating Mode: Modulate inlet damper to maintain minimum airflow setpoint.

4. Fan Control
 - a. Enable/Disable: Enable the fan during heating mode of operation. Disable the fan during cooling mode of operation.

5. Electric Heat
 - a. Enable/Disable: Enable the electric heat during heating mode of operation. Disable the electric heat during cooling mode of operation.
 - b. Heating Mode: Once the inlet damper is maintaining the minimum airflow setpoint, stage the electric heat to maintain space heating setpoint.

6. Alarms: The BAS shall annunciate the following alarms (auto reset):
 - a. High Space Temperature: If the space temperature is 3 °F (adj.) greater than setpoint for a minimum time delay.
 - b. Low Space Temperature: If the space temperature is 3 °F (adj.) less than setpoint for a minimum time delay.

7. Required Reports
 - a. Title: Space Temperature
Frequency: Weekly
Data: Low, high, and average space temperature per day
 - b. Title: Electric Heat Runtime
Frequency: Weekly
Data: The runtime hours per day for each stage of electric heat.



NE BRANCH LIBRARY

FAN POWERED TERMINAL
UNITS - CONTROLS

114 EAST 20th AVENUE, SUITE 2000, FT. LAUDERDALE, FL 33305
 WWW.BFBENGINEERING.COM
 HSE PROJECT NO. 0907
 THIS DOCUMENT IS THE PROPERTY OF BARNETT FRONCZAK BARLOWE ARCHITECTS AND ENGINEERS, INC. IT IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED HEREIN. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF BARNETT FRONCZAK BARLOWE ARCHITECTS AND ENGINEERS, INC.
 Florida Certificate of Authorization #2485



PROJECT	09-27
DATE	12/15/09
DRAWN	REM
CHECKED	DMH/RLC
FILE NO.	.

REV	DATE
△	/ /

DRAWING NO.
C-3
 SHEET
 OF

A-1 SINGLE DUCT VARIABLE VOLUME TERMINAL WITH NO HEAT (VVT):

1. General


- a. The terminal unit shall be controlled by a standalone ASC. The ASC shall monitor and control the unit in a stand-alone mode or as directed by the BAS.
- b. The ASC reside on a sub-network as defined in Article 2.2 "Communications" of Specification 15900.

2. Space Temperature Control

- a. Space Setpoints: Provide a space temperature cooling setpoint. Provide unoccupied cooling setpoint.
- b. Inlet Damper: Provide minimum and maximum airflow setpoints (Initial value: See Terminal Box Schedule). Modulate inlet damper between minimum and maximum airflow setpoints to maintain space setpoint.

3. Unoccupied Operation

- a. Temperature Control: During unoccupied hours reset the cooling setpoint equal to the unoccupied setpoint. Enable unoccupied mode of operation to maintain the unoccupied setpoint. Send signal to respective air handler AAC to initiate unoccupied operation.
- b. Tenant Override: If the override button is activated at the space sensor; then initiate an occupied mode of operation for a minimum time delay. If tenant override is enabled; then send signal to respective air handler AAC to initiate occupied operation.



NE BRANCH LIBRARY

VARIABLE VOLUME
TERMINAL UNITS -
CONTROLS

114 EAST 20 AVENUE, SUITE 200, FT. LAUDERDALE, FL 33301
 TEL: 954.776.0077
 WWW.AB2ENGINEERING.COM

THIS DOCUMENT IS THE PROPERTY OF AB2 ENGINEERING, INC.
 IT IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED IN THE TITLE BLOCK.
 REPRODUCTION OR TRANSMISSION IN ANY FORM OR BY ANY MEANS IS PROHIBITED.

Florida Certificate of Authorization #2485



PROJECT	09-27
DATE	12/15/09
DRAWN	REM
CHECKED	DMH/RLC
FILE NO.	.

REV	DATE
△	/ /

DRAWING NO.
C-4
 SHEET
 OF